

CABLES FOR SERIES A CONTROL UNITS

All cable is contractor supplied.

CABLES FOR SERIES B CONTROL UNITS






Photo	Part No. and Description
	LW-CBL-CAT5-DD-36 3 foot (90 cm) dry location rated CAT5 cable for connection from LightWild control unit to LightWild control unit.
	LW-CBL-CAT5-DD-84 7 foot (210 cm) dry location rated CAT5 cable for connection from LightWild control unit to LightWild control unit.
	LW-CBL-CAT5-DD-168 14 foot (420 cm) dry location rated CAT5 cable for connection from LightWild control unit to LightWild control unit.

Photo	Part No. and Description
	LW-CBL-XLR5M-RJ45-36 3 foot (90 cm) XLR-5 male-to-RJ45 cable. Specify when connecting to a DMX controller with a traditional DMX pinout.
	LW-CBL-XLR5F-RJ45-36 3 foot (90 cm) XLR-5 female-to-RJ45 cable. Specify when connecting to a DMX controller with a traditional DMX pinout.

CABLES FOR SERIES C CONTROL UNITS






Photo	Part No. and Description
	LW-CBL-CAT5-DD-36 3 foot (90 cm) dry location rated CAT5 cable for connection from LightWild control unit to LightWild control unit.
	LW-CBL-CAT5-DD-84 7 foot (210 cm) dry location rated CAT5 cable for connection from LightWild control unit to LightWild control unit.
	LW-CBL-CAT5-DD-168 14 foot (420 cm) dry location rated CAT5 cable for connection from LightWild control unit to LightWild control unit.

Photo	Part No. and Description
	LW-CBL-XLR5M-RJ45-36 3 foot (90 cm) XLR-5 male-to-RJ45 cable. Specify when connecting to a DMX controller with a traditional DMX pinout.
	LW-CBL-XLR5F-RJ45-36 3 foot (90 cm) XLR-5 female-to-RJ45 cable. Specify when connecting to a DMX controller with a traditional DMX pinout.

CABLES FOR SERIES D CONTROL UNITS

LightWild quotation sales will include control cabling in project specific bids.

ALL CABLES ARE UL LISTED.